



Torque ratings for MSP Terminal Blocks

<u>Catalog #'s</u>	<u>Screw Size</u>	<u>Wire Range</u>	<u>Torque (lb-in.)</u>
<u>Single Row</u>			
411	2-56	16-20 AWG (CU)	2.0
599	5-40	16-22 AWG (CU)	9.0
699	6-32	12-20 AWG (solid CU)	9.0
		12-22 AWG (str'd CU)	9.0
812	8-32	12-14 AWG (CU)	16.0
1690	6-32	14 max AWG (CU)	9.6
2590	6-32	16 max AWG (CU)	4.8
2690	6-32 / 8-32	14-16 AWG (CU)	9.6
<u>Double Row</u>			
100 / 670A	6-32	12-20 AWG (solid CU)	9.0
		12-22 AWG (str'd CU)	9.0
200 / 671	6-32	12-20 AWG (solid CU)	9.0
		12-22 AWG (str'd CU)	9.0
200HB	6-32	12-20 AWG (solid CU)	9.0
		12-22 AWG (str'd CU)	9.0
300	8-32	10-14 AWG (CU)	20.0
		12-22 AWG (str'd CU)	20.0
672	8-32	12-14 AWG (CU)	16.0
400	10-32	10-22 AWG (CU)	20.0
410	2-56	18 -20 AWG (CU)	2.0
600	5-40	12-20 AWG (solid CU)	9.0
		12-22 AWG (str'd CU)	9.0
600A	6-32	12-20 AWG (solid CU)	9.0
		12-22 AWG (str'd CU)	9.0
601	6-32	12-20 AWG (solid CU)	9.0
		12-22 AWG (CU)	9.0
602	8-32	12-14 AWG (CU)	16.0
603	10-32	max 10 AWG (CU)	20.0
604	12-32	max 4 AWG (CU)	25.0
605	¼-28	max 2 AWG (CU)	20.0
621 RZ	6-32	12-20 AWG (solid CU)	9.0
		12-22 AWG (str'd CU)	9.0
670A RZ	6-32	14-22 AWG (CU)	9.0
		14-22 AWG (CU)	9.0
671 RZ	6-32	12-20 AWG (solid CU)	9.0
		12-22 AWG (str'd CU)	9.0
672 RZ	8-32	12-14 AWG (CU)	16.0

Please note that the information contained within this document is not considered to be controlled information by Marathon Special Products. This information is subject to change upon Marathon Special Products' discretion and with no notification to customers.

This information is considered for reference only. For exact specification, reference the product label information.