

Power Distribution Block

134x526

Replace "x" with 1, 2, or 3 for number of poles

Wire Range

- Line: (2) 350kcmil - #6
- Load: (3) 2/0 - #14 - Top Row
(3) 2/0 - #8 - Bottom Row

Electrical Ratings

- 620 Amps
- 600V per UL 1953
- Short circuit current ratings (SCCR): See SCCR section below for specifications
- CU7AL - 75°C connector terminal rating with copper or aluminum wire
- Factory & Field Wiring

Agency Compliance


- cULus - UL Listed, investigated to UL 1953, UL File QPOS.E309401 and UL evaluated to CSA 22.2 No 158 File no. QPOS7.309401

Material Information


- Insulator base:
 - Thermoplastic
 - Flammability rating of insulator base UL94V0
 - Insulator base temperature rating: -40°C to 125°C (UL RTI)
- Connector: aluminum, tin plated
- Terminal set screws: aluminum, tin plated
- Connector mounting screws: steel, zinc plated
- RoHS compliant



Termination Specifications

Line Side	Wire Size (CU Stranded)	Torque	Wires / Terminal	Wire Class (UL) ¹
	350 - 300 kcmil	31 N·m (275 lbf·in)	1	B, C
	250 kcmil - #2	31 N·m (275 lbf·in)	1	B, C, G, H, I (DLO)
	#4 - 6	31 N·m (275 lbf·in)	1	B, C

- Wire strip length: 1 in (25mm)
- Terminal screw drive: 5/16 in. hex

Load Side	Wire Size (CU Stranded)	Torque	Wires / Terminal	Wire Class (UL) ¹
	2/0 - 1/0	13.6 N·m (120 lbf·in)	1	B, C
	1 - 6	5.1 N·m (45 lbf·in)	1	B, C, G, H, I (DLO)
	8	4.5 N·m (40 lbf·in)	1 - 2 ²	B, C, G, H, I (DLO)
	10 - 14 (Top row ONLY)	4 N·m (35 lbf·in)	1 - 2	B, C, G, H, I (DLO)

- Solid copper wire range: #10 - 14 AWG (Top row ONLY)
- Wire strip length:
 - top row: 5/8 in. (16mm)
 - bottom row: 1-1/8 in. (28.6mm)
- Terminal screw drive: 3/16 in. hex

¹ For information on copper stranded wire classes please visit:
<http://www.marathonsp.com/CatalogPDFs/Flexible-Stranded-Wire.php>

² Multiple wire rating applies to class B, C, & I.

Short Circuit Current Ratings

- The suitable conductor ranges are limited to the table values only for achieving the SCCR in excess of the default rating of 10,000A.
- Other conductor combinations within the “Terminal Specifications” noted are suitable for achieving a SCCR of 10,000A (the default rating of terminal blocks).
- Enclosure size – For SCCR’s greater than the default of 10KA, the minimum enclosure size is 16x12x6. When using the default rating, there are no enclosure limitations other than proper fit of the product.

Wire Class	Suitable Conductors Copper, Stranded		Overcurrent Protection Fuse Class/Max Amp Rating						SCCR, RMS SYM Amps
	Line	Load	J	T	RK1	RK5	G	CC	
B-C	350 - 4	2/0 - 4	500	500	400	200	60	30	100,000
G, H, I, K, DLO	250 - 2	2 - 6	500	500	400	200	60	30	100,000
(*)	350 - 14	2/0 - 14	None (Default Rating)						10,000

* Any wire class evaluated (see terminal specification section)

Installation & Accessories

- Mounting (Panel):
 - For use with #10 fastener (#8 washer recommended with SHCS)
 - Mounting torque to be determined in end use application not to exceed 30 in lbs (3.4 Nm)
- Cover:
 - Snap on hinge cover available upon request
 - Catalog number:
 - For 3-Pole (1343xxx), CH1343
 - For 2-Pole (1342xxx), CH1341 (2x for each pole)
 - For 1-Pole (1341xxx), CH1341
 - Covers are black thermoplastic

Drawing

