

## POWER TERMINAL BLOCK

# 134x554

Replace "x" with 1, 2, or 3 for number of poles



### Wire Range

- Line: (1) 350kcmil - #6 AWG
- Load: (2) 2/0 - #14 AWG

### Electrical Ratings

- 310 Amps
- 600V per UL 1059 & CSA 22.2 No.158, class B & C requirements
- Short circuit current ratings (SCCR): See SCCR section below for specifications.
- CU7AL - 75°C connector terminal rating with copper or aluminum wire
- Factory & Field Wiring


### Agency Compliance

- UL Listed, Investigated to UL 1953, File QPQS7.E309401


### Material Information

- Insulator base:
  - Thermoplastic
  - Flammability rating of insulator base UL94V0
  - Insulator base temperature rating: -40°C to 125°C (UL RTI)
- Connector: aluminum, tin plated
- Terminal screws: aluminum, tin plated
- Connector mounting screws: steel, zinc plated
- RoHS compliant

**Termination Specifications**

Line Side	Wire Size (CU Stranded)	Torque	Wires / Terminal	Wire Class (UL) <sup>1</sup>
	350 - 300 kcmil	31 N·m (275 lbf·in)	1	B, C
	250 - 2	31 N·m (275 lbf·in)	1	B, C, G, H, I (DLO)
	4 - 6	31 N·m (275 lbf·in)	1	B, C

- Aluminum wire range: 350kcmil - #6
- Wire strip length: 1.0 in. (25mm)
- Terminal screw drive: 5/16 in. hex

Load Side	Wire Size (CU Stranded)	Torque	Wires / Terminal	Wire Class (UL) <sup>1</sup>
	2/0 - 1/0	13.6 N·m (120 lbf·in)	1	B, C
	1 - 6	13.6 N·m (120 lbf·in)	1	B, C, G, H, I (DLO)
	8	4.5 N·m (40 lbf·in)	1	B, C, G, H, I (DLO)
	10 - 14	4 N·m (35 lbf·in)	1	B, C, I (DLO)

- Solid copper wire range: #10 - 14 AWG
- Aluminum wire range: 2/0 - #8
- Wire strip length: 1.0 in. (25mm)
- Terminal screw drive: 3/16 in. hex

<sup>1</sup> For information on copper stranded wire classes please visit:  
<http://www.marathonsp.com/flexible-stranded-wire.php>

## Short Circuit Current Ratings (SCCR)

- The suitable conductor ranges are limited to the table values only for achieving the SCCR in excess of the default rating of 10,000A.
- Other conductor combinations within the “Terminal Specifications” noted are suitable for achieving a SCCR of 10,000A (the default rating of terminal blocks).
- Enclosure size – For SCCR’s greater than the default of 10KA, the minimum enclosure size is 16x12x6. When using the default rating, there are no enclosure limitations other than proper fit of the product.

### SCCR With Fuses

Wire Class	Suitable Conductors		Max Overcurrent Protection <b>Fuse</b> Required Amp Rating / Class						SCCR RMS Sym. Amps 600V. Max
	Line	Load	J	T	RK1	RK5	G	CC	
B, C	350 - 3/0	2/0 - 1	500	500	400	200	60	30	100,000
B, C	350 - 6	2/0 - 10	200	200	200	100	60	30	100,000
G, H, I	250 - 1/0	1 - 10	150	150	100	30	60	30	100,000
(*)	350 - 6	2/0 - 14	None (Default Rating)						10,000

\* Any wire class evaluated (see terminal specification section)

## Installation & Accessories

- Mounting (Panel):
  - For use with #10 fastener. ( #8 washer recommended with SHCS)
  - Mounting torque to be determined in end use application not to exceed 30 in lbs (3.4 N.m)
- Cover:
  - Snap on hinge cover available upon request
  - Catalog number:
    - For 3-Pole (1343xxx), CH1343
    - For 2-Pole (1342xxx), CH1342
    - For 1-Pole (1341xxx), CH1341
  - Cover is back thermoplastic

**Drawing**

