

Product Data Sheet



POWER DISTRIBUTION BLOCK

134x572

Replace "x" with 1, 2, or 3 for number of poles



Wire Range

- Line: (1) 3/0 - #14 AWG (70mm² - 2.5mm²)
- Load: (1) 3/0 - #14 AWG (70mm² - 2.5mm²)

Electrical Ratings

- 200 Amps
- 600V per UL 1953 & CSA 22.2 No.158, class B & C requirements
- Short Circuit Current Rating (SCCR): See SCCR section for specifications
- CU7AL - 75°C connector terminal rating with copper or aluminum wire
- Factory & Field Wiring


Agency Compliance

- cULus - UL Listed, investigated to UL 1953, UL File QPQS.E309401 and UL evaluated to CSA 22.2 No 158 File no. QPQS7.309401

Material Information

- Insulator base:
 - Thermoplastic
 - Flammability rating of insulator base UL94V0
 - Insulator base temperature rating: -40°C to 125°C (UL RTI)
- Connector: aluminum, tin plated
- Line terminal set screws: aluminum, tin plated
- Load terminal set screw: steel, zinc plated
- Connector mounting screws: steel, zinc plated
- RoHS compliant

Termination Specifications

Line and Load Side	Wire Size (CU Stranded)	Torque	Wires / Terminal	Wire Class (UL) ¹
	3/0	20.3 N.m (180 lbf in)	1	B, C
	2/0 - 2	20.3 N.m (180 lbf in)	1	B, C, G, H, I (DLO)
	4	20.3 N.m (180 lbf in)	1	G, H, I (DLO)
			1 - 2	B, C
	6 - 8	20.3 N.m (180 lbf in)	1 - 2	B, C, G, H, I (DLO)
	10	5.6 N.m (50 lbf. in)	1 - 4	B, C
			1 - 2	G, H, I (DLO)
	12 - 14	5.6 N.m (50 lbf. in)	1 - 4	B, C
1			G, H, I (DLO)	

- Aluminum stranded wire range: 3/0 - #6 AWG
- Wire strip length: 7/8 in. (18mm)
- Copper solid wire range: #10 - #14
- Terminal screw drive: 1/4" Hex

¹ For information on copper stranded wire classes please visit:
<http://www.marathonsp.com/flexible-stranded-wire.php>

Short Circuit Current Ratings (SCCR)

- The suitable conductor ranges are limited to the table values only for achieving the SCCR in excess of the default rating of 10,000A.
- Other conductor combinations within the “Terminal Specifications” noted are suitable for achieving a SCCR of 10,000A (the default rating of terminal blocks).
- Enclosure size – For SCCR’s greater than the default of 10KA, the minimum enclosure size is 16x12x6. When using the default rating, there are no enclosure limitations other than proper fit of the product.

Wire Class	Suitable Conductors		Max Overcurrent Protection Fuse Required Amp Rating / Class						SCCR RMS Sym. Amps 600V. Max
	Line	Load	J	T	RK1	RK5	G	CC	
B, C	3/0 - 8	3/0 - 8	300	300	200	100	60	30	100,000
G, H, I (DLO)	2/0 - 8	2/0 - 8	300	300	200	100	60	30	100,000
*	3/0 - 14	3/0 - 14	None (Default Rating)						10,000

* Any wire class evaluated (see terminal specification section)

Installation & Accessories

- Mounting (Panel):
 - For use with #10 fastener. (#8 washer recommended with SHCS)
 - Mounting torque to be determined in end use application not to exceed 30 in lbs (3.4 N.m)

- Cover:
 - Snap on hinge cover available upon request
 - Catalog number:
 - For 3-Pole (1343xxx), CH1343
 - For 2-Pole (1342xxx), CH1341 (2x For each pole)
 - For 1-Pole (1341xxx), CH1341
 - Cover is back thermoplastic

Drawing

