

## POWER DISTRIBUTION BLOCK

# 134x596

Replace "x" with 1, 2, or 3 for number of poles



### Wire Range

- Line: (2) 250 kcmil - 6 (120mm<sup>2</sup> - 16mm<sup>2</sup>)
- Load: (12) #4 - 14 AWG (16mm<sup>2</sup> - 2.5mm<sup>2</sup>)

### Electrical Ratings

- 510 Amps
- 600V per UL 1953 & CSA 22.2 No.158, class B & C requirements
- Short circuit current ratings (SCCR): See SCCR section below for specifications.
- CU7AL - 75°C connector terminal rating with copper or aluminum wire
- Factory & Field Wiring


### Agency Compliance

- cULus - UL Listed, investigated to UL 1953, UL File QPQS.E309401 and UL evaluated to CSA 22.2 No 158 File no. QPQS7.309401


### Material Information

- Insulator base:
  - Thermoplastic
  - Flammability rating of insulator base UL94V0
  - Insulator base temperature rating: -40°C to 125°C (UL RTI)
- Connector: aluminum, tin plated
- Line terminal set screws: aluminum, tin plated
- Load terminal set screw: steel, nickel plated
- Connector mounting screws: steel, zinc plated
- RoHS compliant

## Termination Specifications

Line Side	Wire Size (CU Stranded)	Torque	Wires / Terminal	Wire Class (UL) <sup>1</sup>
	250 kcmil	31.1 N·m (275 lbf·in)	1	B, C
	4/0 - 1	31.1 N·m (275 lbf·in)	1	B, C, G, H, I (DLO)
	2 - 6	31.1 N·m (275 lbf·in)	1	G, H, I (DLO)
			1 - 2	B, C

- Aluminum stranded wire range: 250 kcmil - #6
- Copper solid wire range: #10 - #14
- Wire strip length: 1 9/16in. (40mm)
- Terminal screw drive: 5/16 in. hex

Load Side	Wire Size (CU Stranded)	Torque	Wires / Terminal	Wire Class (UL) <sup>1</sup>
	4 AWG	4 N·m (35 lbf·in)	1	B, C
	6 - 8	4 N·m (35 lbf·in)	1	B, C, G, H, I (DLO)
	10	4 N·m (35 lbf·in)	1-2	B, C, G, H, I (DLO)
	12 - 14	4 N·m (35 lbf·in)	1-4	B, C
			1-2	G, H, I (DLO)

- Aluminum stranded wire range: #4 - 6 AWG
- Solid copper wire range: #10 - #14 AWG
- Wire strip length:
  - top row: 1/2 in. (13mm)
  - middle row: 11/16 in. (18mm)
  - bottom row: 15/16 in. (24mm)
- Terminal screw drive: 1/8 in. hex

<sup>1</sup> For information on copper stranded wire classes please visit:  
<http://www.marathonsp.com/flexible-stranded-wire.php>

## Short Circuit Current Ratings (SCCR)

- The suitable conductor ranges are limited to the table values only for achieving the SCCR in excess of the default rating of 10,000A.
- Other conductor combinations within the “Terminal Specifications” noted are suitable for achieving a SCCR of 10,000A (the default rating of terminal blocks).
- Enclosure size – For SCCR’s greater than the default of 10KA, the minimum enclosure size is 16x12x6. When using the default rating, there are no enclosure limitations other than proper fit of the product.

Wire Type	Suitable Conductors Copper, Stranded		Overcurrent Protection Fuse Class/Max Amp Rating						SCCR, RMS SYM Amps
	Line	Load	J	T	RK1	RK5	G	CC	
B - C	250 - 4	4 - 10	400	400	400	100	60	30	100,000
B - C	250 - 6	4 - 14	150	150	100	30	60	30	
G, H, I	3/0 - 4	6 - 10	400	400	400	100	60	30	
G, H, I	3/0 - 6	6 - 14	150	150	100	30	60	30	
*	250 - 6	4 - 14	None (Default Rating)						10,000

\* Any wire class evaluated (see terminal specification section)

## Installation & Accessories

- Mounting (Panel):
  - For use with #10 fastener.(#8 washer recommended with SHCS)
  - Mounting torque to be determined in end use application not to exceed 30 lbf-in (3.4 N-m).
- Cover:
  - Snap on, hinge cover available on request
  - Catalog number:
    - For 3-Pole (1343xxx), CH1343
    - For 2-Pole (1342xxx), CH1341 (2x For each pole)
    - For 1-Pole (1341xxx), CH1341
  - Cover black thermoplastic

Drawing

