

## POWER DISTRIBUTION BLOCK

# 135X707

Replace "X" with 1, 2, 3 for number of poles

### Wire Range

- Line Side: (2) 750 kcmil - 1/0 AWG
- Load Side: (5) 250 kcmil - 6 AWG and ( ) #2 - #14 AWG

### Electrical Ratings:

- 950 Amps
- 600 Volts AC/DC (UL 1953)
- Factory and Field Wiring

### Agency Compliance


- UL Listed, Investigated to UL 1953, File QPQS.E309401

### Material Information


- Insulator base:
  - Thermoplastic
  - Temperature rating: 125° C (265° F)
  - Flammability rating of insulator base: UL 94 V-0
- Connector - plated aluminum
- Connector mounting screw: plated steel
- RoHS Compliant



Termination Specifications

Line Side	Wire Size (CU Stranded)	Torque	Wires/ Terminal	Wire Class (UL) <sup>1</sup>
	750 - 1/0	67.8 N.m (600 in. lbs)	1	B, C
	535 - 1/0	67.8 N.m (600 in. lbs)	1	G, H, I

- Aluminum stranded wire range: 750 - 1/0
- Solid copper wire range: 750 - 1/0
- Wire strip length: 1 3/4"
- Terminal screw drive: 5/16 in. hex

Load Side	Terminal	Wire Size (CU Stranded)	Torque	Wires/Terminal	Wire Class (UL) <sup>1</sup>
	3/0 - 6AWG	3/0	20.3 N.m (180 in. lbs)	1	B, C
		2/0 - 6	20.3 N.m (180 in. lbs)	1	B, C, G, H, I
	2 - 14 AWG	2 - 3	5.7 N.m (50 in. lbs)	1	B, C
		4 - 8	5.7 N.m (50 in. lbs)	1	B, C, G, H, I
		10 - 14	4.5 N.m (40 in. lbs)	1	B, C, I

- Aluminum stranded wire range: 3/0 - 6 AWG
- Solid copper wire range: 3/0 - 6 AWG
- Wire strip length 3/0: 1 3/4"
- Wire strip length #2 AWG Top Row: 7/16"
- Terminal screw drive: 5/16 in. hex

<sup>1</sup> For information on copper stranded wire classes please visit:  
<http://www.marathonsp.com/flexible-stranded-wire.php>

Short Circuit Current Ratings (SCCR)

- The suitable conductor ranges are limited to the table values only for achieving the SCCR in excess of the default rating of 10,000A.
- Other conductor combinations within the “Terminal Specifications” noted are suitable for achieving a SCCR of 10,000A (the default rating of terminal blocks).
- Enclosure size – Investigated with a minimum 20x24x8 enclosure. Use in smaller enclosures is subject to end use evaluation.
- SCCR Ratings apply for Copper Stranded wire only

Wire Class	Suitable Conductors Copper, Stranded		Overcurrent Protection Fuse Class/Max Amp Rating						SCCR, RMS SYM Amps
	Line	Load - *L/S	J	T	RK1	RK5	G	CC	
B, C	750 - 1/0	3/0 - 2 (L)	600	700	600	200	60	30	100,000
		3/0 - 6 (L)	300	300	200	100	60	30	
		2 - 6 - (S)	300	300	200	100	60	30	
G, H, I	535 - 1/0	2/0 - 2 (L)	500	500	400	200	60	30	
		3/0 - 6 (L)	300	300	200	100	60	30	
		4 - 6 (S)	300	300	200	100	60	30	

\*L = Large Opening

\*S = Small Opening

## Installation and Accessories

- Mounting (Panel)

For use with 1/4" fasteners (4 pole)

Mounting torque to be determined in end use application not to exceed 30 in. lbs. (3.4 N.m)

- Covers

Catalog number CH1351

One Cover per pole (Ex: 1353707 ) would need (3) CH1351's

Covers are black polycarbonate

g

## Drawing

