


Product Data Sheet



6R200AXBE

Replace "X" with 1 or 3 for number of poles

Reinforced Class R Fuse Holder 200 Amps, 600 Volts AC/DC



Wire Range:

- 250 kcmil - #6 AWG Copper
- 250 kcmil - #6 AWG Aluminum

Holds fuse size 1 3/4" diameter X 9 5/8"

Commonly used fuses in this holder: A6D-R, A6K-R, DLS-R, FLSR, FLSR_ID, FRS-R, IDSR, KLSR, KTS-R, LLSRK, LLSRK_ID, LPS-RK, TRS-R

[See table below for wire sizes.](#)

Electrical Ratings:

- 101 - 200A max (amperage rating based on maximum fuse rating for that physical size)
- 600 Volts AC/DC
- Approved for 200,000 Amp Withstand Rating

Mechanical Ratings:

- Maximum insulator base temperature: 130°C (266°F) UL RTI
- Flammability rating of insulator base: UL 94 V-0
 - Use outside these ratings needs to be judged in the end-use application.

Materials:

- Fuse Clip: Aluminum, Tin plated
- Box Connector: High conductivity aluminum, Tin plated
- Reinforcing Spring: Stainless Steel
- Pin Spring: Steel, Zinc plated
- Insulator base: Thermoset Polyester
- Terminal set screws: Aluminum, Tin plated
- Connector mounting screws: Steel, zinc plated

Agency Approvals:


- UL Listed, Fuseholder standards UL 4248-1 and UL 4248-12.
- UL File No. IZLT.E35113
- CSA Certified, CSA C22.2 No. 39 – M1987, File No. LR21455
- CE compliant to IEC 60947-1
- RoHS Compliant

Wire Approvals:

Wire Size	Torque		Copper Wire Stranding Classes - Number of Conductors		
	N-m	In. lbs	Solid	Class B	Class C
250 kcmil	37.1	275		1	1
4/0	37.1	275		1	1
3/0	37.1	275		1	1
2/0	37.1	275		1	1
1/0	37.1	275		1	1
1	37.1	275		1	1
2	37.1	275		1	1
4	37.1	275		1	1
6	37.1	275		1	1

Aluminum stranded wire range: 250 kcmil - #6 AWG.

- Wire strip length – 1 5/16”
- Hex key required: 5/16”
- Panel mountable: # 1/4” fastener, torque to 30 - 40 in. lbs.(3.4 - 4.5 N-m)



WWW.MARATHONSP.COM
1-419-352-8441