

Class T Fuse Holder

6T30AXS

Replace "X" with 2 or 3 for number of poles

Holds fuse size 9/16" diameter X 1 1/2"

Commonly used fuses in this holder: A6T, JJS, JLLS



Wire Range

- #10 - #22 AWG CU

Electrical Ratings

- 0 - 30A Max (Amperage rating based on maximum fuse rating for that physical size)
- 600 Volts AC
- Approved for 200,000 Amp Withstand Rating


Agency Compliance

- UL Listed, Fuseholder standards UL 4248-1 and UL 4248-15.
- UL File No. IZLT.E35113
- CSA Certified: 22.2 No 39 - M1987, File No. LR21455
- CE compliant to IEC 60947-1
- RoHS Compliant

Material Information

- Insulator base temperature rating: -40°C/F to 150°C (302°F) UL RTI
- Flammability rating of insulator base: UL 94 V-0
- Use outside these ratings needs to be judged in the end-use application.
- Fuse Clip: Copper alloy, tin plated
- Insulator base: Phenolic
- Terminal set screws: Aluminum, nickel plated
- Connector mounting screws: Steel, zinc plated

Termination Specifications

Line and Load Side	Wire Size (CU Stranded)	Torque	Wires/ Terminal	Wire Class (UL)
	#10 - #18	2.8 N.m (25 in. lbs)	1	Solid CU, B, C
	#20 - #22	2.8 N.m (25 in. lbs)	1	B, C

- Wire Strip length - 9/16"

Installation & Accessories

- Mounting (Panel):
 - #10 fastener, mounting torque to be determined in end-use application. Not to exceed 20 lbf. (2.2 N-m)

Drawing

