

GROUNDING LUG

WC12044 - Part No.9740701



Wire Range

- Primary Side
 - (1) #2/0 - #14 AWG CU
 - (1) #2/0 - #6 AWG AI
- Secondary Side
 - (4) #4 - #14 AWG Cu
 - (4) #4 - 6 AWG AI
 - See tables below for Flexible stranded approvals
 - Rated for use with 75°C wire per NEC Code


Agency Compliance

- UL Recognized Wire Connector - File ZMVV2.E43665
- Final acceptance of this component is dependent upon its installation and use in complete equipment submitted to UL
- CSA Certified, CSA File No. 63510-25 (Wire Classes B & C only)
- RoHS Compliant


Material Information

- Connector: Aluminum, tin plated
- Terminal screws:
 - Primary Side: Line Side: Aluminum, tin plated, 3/16 Hex Socket Drive
 - Secondary Side: Load Side: Steel, nickel plated 1/8 Hex Socket Drive

Termination Specifications

Primary Side	Wire Size (CU Stranded)	Torque	Wires / Terminal	Wire Class (UL) ¹
	2/0 - 1/0	120 in. lbs	1	B, C,
	1 - 6	120 in. lbs	1	B, C, G, H, I
	8	40 in. lbs	1	B, C, G, H, I
	10 - 14	35 in. lbs	1	B, C, I

- Aluminum stranded wire range: 2/0 - #6 AWG
- Solid Copper wire range: #10 - #14 AWG
- Wire Strip length: 3/4 in. (19 mm)

Secondary Side	Wire Size (CU Stranded)	Torque	Wires / Terminal	Wire Class (UL) ¹
	4 AWG	35 in. lbs	1	B, C
	6 - 8	35 in. lbs	1	B, C, G, H, I
	10	35 in. lbs	1 - 2	B, C
	12 - 14	35 in. lbs	1 - 4	B, C
			1 - 2	I

- Aluminum stranded wire range: #4 - #6 AWG
- Solid Copper wire range : #10 - #14 AWG
- Wire Strip length: Top Row: 3/8 in (10mm)
Bottom Row: 3/4 in (19mm)

Panel Mountable: #10 or M5 fastener

Drawing

