

## Class CC Fuse Holder **ZTx419**

Replace "x" with 1, 2 or 3 for number of poles.  
Enclosed, with Push-In Terminals.  
For use with CC fuses only.

### Wire Range

- 8 - #18 AWG, Push-in Terminals for:
  - Stranded Wire

### Electrical Ratings

- 30 Amps max
- 600 Volts (AC/DC)
- Withstand Rating (SC) 200kA
- Factory & Field Wiring

### Agency Compliance


- cULus - UL Listed, investigated to UL 1953, UL file IZLT.E35113 and evaluated to CSA 22.2 No 4248
- CE compliant to IEC 60947-1
- IEC 60529 degree of protection IP20

### Material Information

- Insulator base & plastic components:
  - Glass filled polyamide
  - Flammability rating of insulator base UL94 V-2
  - Insulator base temperature rating: -40°C to 130°C (UL RTI)
- Fuseclips & Contacts - plated copper
- Springs - plated steel
- RoHS compliant



## Termination Specifications

Load Side	Wire Type/Class	Wire Size (CU Stranded)	Wires / Terminal	Wire Strip Length
	Stranded Bare (B,C)	#8-18 AWG	1	.50 in
	Ferruled Wire	#8-18 AWG	1	
	Solid Bare	#10 - 18	1	

## Installation & Accessories

- Din-Rail mountable on (any) 35mm wide rail: MN35-2 (35 X 7.5mm, 2m long)
- End Brackets: MSK35
- Load Terminal Wire removal
  - For use with a flat-blade screw driver width .21" max.
  - Press the flat of the screw driver down full until you feel the terminal open up.
  - Pull wire out.
  - Recut & restrip before reuse

## Drawing

