

## 10X38mm Fuse Holder **ZTx420**

Replace "x" with 1, 2 or 3 for number of poles.  
Enclosed, with Push-In Terminals.  
For use with 10x38mm fuses only.

### Wire Range

- 8 - #18 AWG, Push-in Terminals for:
  - #10-14 awg UL Listed ferrule
  - #10-14 awg solid wire

### Electrical Ratings

- 30 Amps max
- 600 Volts (AC/DC)
- Withstand Rating (SC) 200kA
- Factory & Field Wiring

### Agency Compliance


- cURus - UL Recognized investigated to UL 1953, UL file IZLT2.E35113 and evaluated to CSA 22.2 No 4248
- CE compliant to IEC 60947-1
- IEC 60529 degree of protection IP20

### Material Information

- Insulator base & plastic components:
  - Glass filled polyamide
  - Flammability rating of insulator base UL94 V-2
  - Insulator base temperature rating: -40°C to 130°C (UL RTI)
- Fuseclips & Contacts - plated copper
- Springs - plated steel
- RoHS compliant



**Termination Specifications**

Load Side	Wire Type/Class	Wire Size (CU Stranded)	Wires / Terminal	Wire Strip Length
	Stranded Bare (B,C)	#8-18 AWG	1	.50 in
	Ferrule	#10-14 AWG	1	N/A
	Solid	#10-14 AWG	1	.50 in

**Installation & Accessories**

- Din-Rail mountable on (any) 35mm wide rail: MN35-2 (35 X 7.5mm, 2m long)
- End Brackets: MSK35
- Load Terminal Wire removal
  - For use with a flat-blade screw driver width a .21 max.
  - Press the flat of the screw driver down full until you feel the terminal open up.
  - Pull wire out.
  - Recut & restrip before reuse

**Drawing**

