







































































High SCCR with Fuse Protection

UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS										UL	FILE UL FILE NO
Marathon Catalog #	Poles	Amps	Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) ⁽²⁾			Overcurrent Protection Fuse Required Class/Max Amp Rating ⁽³⁾						SCCR, RMS SYM Amps ⁽¹⁾		
			Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC			
1321570	1						2/0-6	4-10	B, C	200	200	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1322570	2	175	(1) 2/0 - 14	(4) 4 - 14			2/0-10	4-14	B, C	150	150	100	30	60	30	100,000 A		
1323570	3						1-6	6-10	G, H, I	150	150	100	30	60	30	100,000 A		
1321572	1						2/0-6	2/0-6	B, C	200	200	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1322572	2	175	(1) 2/0 - 14	(1) 2/0 - 14			1-6	1-6	G, H, I	150	150	100	30	60	30	100,000 A		
1323572	3																	
1321574	1						2/0-6	2/0-6	B, C	300	300	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1322574	2	175	(1) 2/0 - 14	(1) 1/4 - 20 x 1/2			2/0-10	8-10	B, C	150	150	100	30	60	30	100,000 A		
1323574	3						1-6	1-6	G, H, I	150	150	100	30	60	30	100,000 A		
1321580	1						2/0-6	4-12	B, C	200	200	100	60	60	30	100,000 A	Recognized	XCFR2.E62806
1322580	2	175	(1) 2/0 - 14	(6) 4 - 14			2/0-10	4-14	B, C	150	150	100	30	60	30	100,000 A		
1323580	3						1-6	6-10	G, H, I	150	150	100	30	60	30	100,000 A		
1321970	1						2/0-6	4-10	B, C	200	200	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1322970	2	175	(1) 2/0 - 14	(4) 4 - 14			1-6	6-10	G, H, I	150	150	100	30	60	30	100,000 A		
1323970	3																	
1321972	1						2/0-6	2/0-6	B, C	300	300	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1322972	2	175	(1) 2/0 - 14	(1) 2/0 - 14			1-6	6-14	G, H, I	150	150	100	30	60	30	100,000 A		
1323972	3																	
1331320	1						250-1/0	250-1/0	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1332320	2	510	(2) 250 - 1/0	(2) 250 - 1/0			3/0-1/0	3/0-1/0	G, H, I	500	500	400	200	60	30	100,000 A		
1333320	3																	
1331360	1						600-2	600-2	B, C	600	600					50,000,A	Recognized	XCFR2.E62806
1332360	2	420	(1) 600 - 2	(1) 600 - 2			600-2	600-2	B, C	400	400	400	200	60	30	100,000,A		
1333360	3						350-2	350-2	G, H, I	400	400	400	200	60	30	100,000,A		
1331552	1						400-3/0	2-8	B, C	400	400	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1332552	2	335	(1) 400 - 6	(4) 2 - 14			400-6	2-8	B, C	200	200	200	100	60	30	100,000 A		
1333552	3						250-1/0	1-6	G, H, I	150	150	100	30	60	30	100,000 A		



































High SCCR with Fuse Protection

UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS										UL	FILE UL FILE NO
Marathon Catalog #	Poles	Amps	Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) ⁽²⁾			Overcurrent Protection Fuse Required Class/Max Amp Rating ⁽³⁾						SCCR, RMS SYM Amps ⁽¹⁾		
			Line	Load	Line	Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC			
1331554	1						350-3/0	2/0-1	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1332554	2	310	(1) 350 - 6	(2) 2/0 - 14			350-6	2/0-10	B, C	200	200	200	100	60	30	100,000 A		
1333554	3						250-1/0	1-10	G, H, I	150	150	100	30	60	30	100,000 A		
1331555	1						2/0-2	4-8	B, C	400	400	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1332555	2	350	(2) 2/0 - 14	(6) 4 - 14			2/0-6	4-10	B, C	200	200	200	100	60	30	100,000 A		
1333555	3						1-6	6-10	G, H, I	150	150	100	30	60	30	100,000 A		
1331559	1						350-4	350-4	B, C	400	400	400	100	60	30	65,000 A	Recognized	XCFR2.E62806
1332559	2	310	(1) 350 - 6	(1) 3/8 - 16 x 1/4			250-4	250-4	G, H, I	300	300	200	100	60	30	65,000 A		
1333559	3																	
1331575	1						600 - 2	2/0 - 10	B, C	400	400	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1332575	2	420	(1) 600 - 2	(4) 2/0 - 14														
1333575	3																	
1331585	1						600-3/0	2-8	B, C	400	400	400	200	60	30	100,000,A	Recognized	XCFR2.E62806
1332585	2	420	(1) 600 - 2	(8) 2 - 14			600-2	2-10	B, C	200	200	200	100	60	30	100,000,A		
1333585	3						350-2	4-10	G, H, I	150	150	100	30	60	30	100,000,A		
1331587	1			(3) 2 - 14			500-3/0	350-6	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1332587	2						500-4	2-10	B, C	200	200	200	100	60	30	100,000 A		
1333587	3	380	(1) 500 - 4	(1) 350 - 6			350-2	1-6	G, H, I	500	500	400	200	60	30	100,000 A		
							350-2	1-10	G, H, I	200	200	200	100	60	30	100,000 A		
1331588	1						600-3/0	1/0-8	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1332588	2	420	(1) 600 - 2	(6) 2 - 14			600-2	1/0-10	B, C	200	200	200	100	60	30	100,000 A		
1333588	3			(3) 1/0 - 14			350-2	1-8	G, H, I	500	500	400	200	60	30	100,000 A		
							350-2	1-10	G, H, I	200	200	200	100	60	30	100,000 A		
1331595	1						600-3/0	4-8	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1332595	2	420	(1) 600 - 2	(12) 4 - 14			600-2	4-10	B, C	200	200	200	100	60	30	100,000 A		
1333595	3						350-2	6-10	G, H, I	150	150	100	30	60	30	100,000 A		

















High SCCR with Fuse Protection

UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS										UL	FILE UL FILE NO
Marathon Catalog #	Poles	Amps	Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) ⁽²⁾			Overcurrent Protection Fuse Required Class/Max Amp Rating ⁽³⁾						SCCR, RMS SYM Amps (1)		
			Line	Load	Line	Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC			
1331596	1						250-1/0	4-10	B, C	450	450	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1332596	2	510	(2) 250 - 6	(12) 4 - 14			3/0-1/0	6-14	G, H, I	150	150	100	30	60	30	100,000 A		
1333596	3																	
1331597	1						250-1/0	2-8	B, C	350	350	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1332597	2	510	(2) 250 - 1/0	(8) 2 - 14			3/0-1/0	4-14	G, H, I	150	150	100	30	60	30	100,000 A		
1333597	3																	
1331953	1						500-3/0	2-10	B, C	400	400	400	100	60	30	100,000,A	Recognized	XCFR2.E62806
1332953	2	380	(1) 500 - 4	(6) 2 - 14			500-4	2-10	B, C	200	200	200	100	60	30	100,000,A		
1333953	3						350-2	4-10	G, H, I	150	150	100	30	60	30	100,000,A		
1331955	1						2/0-2	4/8	B, C	400	400	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1332955	2	350	(2) 2/0 - 14	(6) 4 - 14			2/0-6	4-10	B, C	200	200	200	60	60	30	100,000 A		
1333955	3						1-6	6-10	G, H, I	150	150	100	30	60	30	100,000 A		
1402401	2						2/0-6	4-14	B, C	200	200	100	100	60	30	100,000 A	Recognized	XCFR2.E62806
1403401	3	175	(1) 2/0 - 14	(6) 4 - 14			2/0-10	4-14	B, C	150	150	100	30	60	30	100,000 A		
							1-10	6-14	G, H, I	60	60	60	30		30	100,000 A		
1402402	2						2/0-6	4-10	B, C	200	200	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1403402	3	175	(1) 2/0 - 14	(4) 4 - 14			1-6	6-10	G, H, I	150	150	100	30	60	30	100,000 A		
1402404	2						350-3/0	4-8	B, C	400	400	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1403404	3	310	(1) 350 - 6	(6) 4 - 14			350-6	4-10	B, C	250	250	200	100	60	30	100,000 A		
							250-6	6-10	G, H, I	150	150	100	30	60	30	100,000 A		
1411300	1						2-6	2-6	B, C	200	200	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1412300	2						2-10	2-10	B, C	100	100	100	30	60	30	100,000 A		
1413300	3	115	(1) 2 - 14	(1) 2 - 14			2-10	2-10	B, C	125	125	60	30	60	30	65,000 A		
1414300	4						4-10	4-10	G, H, I	150	150	100	30	60	30	100,000 A		

















High SCCR with Fuse Protection

UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS										UL	FILE UL FILE NO
Marathon Catalog #	Poles	Amps	Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) ⁽²⁾			Overcurrent Protection Fuse Required Class/Max Amp Rating ⁽³⁾						SCCR, RMS SYM Amps ⁽¹⁾		
			Line	Load	Line	Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC			
1411400	1	115	(1) 2 - 14	(4) 10 - 16			2-6	10	B, C	200	200	200	60	60	30	100,000 A		
1412400	2						2-10	10-14	B, C	150	150	100	30	60	30	100,000 A		
1413400	3						2-12	10-14	B, C	60	60	30		50	30	100,000 A		
1414400	4						4-10	10-14	G, H, I	150	150	100	30	60	30	100,000 A		
1421120	1	175	(1) 2/0 - 14	(1) 2/0 - 14			2/0-6	2/0-6	B, C	300	300	200	100	60	30	65,000 A		
1422120	2						1-6	1-6	G, H, I	300	300	200	100	60	30	65,000 A		
1423120	3																	
1421121	1	150	(1) 1/0 - 18	(1) 1/0 - 18			1/0-6	1/0-6	B, C	175	175	100	60	60	30	100,000 A		
1422121	2						1-6	1-6	G, H, I	175	175	100	60	60	30	100,000 A		
1423121	3																	
1421552	1	115	(1) 2 - 14	(1) 2 - 14			2-6	2-6	B, C	300	300	200	100	60	30	100,000 A		
1422552	2						2-10	2-10	B, C	150	150	100	30	60	30	100,000 A		
1423552	3						2-10	2-10	B, C	200	200	100	30	60	30	65,000 A		
	3						4-10	4-10	G, H, I	150	150	100	30	60	30	100,000 A		
1421553	1	175	(1) 2/0 - 14	(1) 1/4-20 X 1/2			2/0-6	2/0-6	B, C	200	200	200	100	60	30	100,000 A		
1422553	2						2/0-10	2/0-10	B, C	100	100	100	30	60	30	100,000 A		
1423553	3						1-6	1-6	G, H, I	150	150	100	30	60	30	100,000 A		
1421570	1	175	(1) 2/0 - 14	(4) 4 - 14			2/0-6	4-10	B, C	200	200	200	100	60	30	100,000 A		
1422570	2						2/0-10	4-14	B, C	150	150	100	30	60	30	100,000 A		
1423570	3						(1) 6	(2) 12 or 14	B, C	225	225	100	60	60	30	100,000 A		
	3						1-6	6-12	G, H, I	150	150	100	30	60	30	100,000 A		
1421572	1	175	(1) 2/0 - 14	(1) 2/0 - 14			2/0-6	2/0-6	B, C	300	300	200	100	60	30	65,000 A		
1422572	2						1-6	1-6	G, H, I	300	300	200	100	60	30	65,000 A		
1423572	3																	
1421574	1	175	(1) 2/0 - 14	(1) 1/4-20 X 1/2			2/0-6	2/0-6	B, C	200	200	200	100	60	30	100,000 A		
1422574	2						2/0-10	2/0-10	B, C	100	100	100	30	60	30	100,000 A		
1423574	3						1-6	1-6	G, H, I	150	150	100	30	60	30	100,000 A		

High SCCR with Fuse Protection

UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS										UL	FILE UL FILE NO
Marathon Catalog #	Poles	Amps	Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) ⁽²⁾			Overcurrent Protection Fuse Required Class/Max Amp Rating ⁽³⁾						SCCR, RMS SYM Amps ⁽¹⁾		
			Line	Load	Line	Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC			
1421970	1	175	(1) 2/0 - 14	(4) 4 - 14			2/0-6	4-10	B, C	200	200	200	100	60	30	100,000 A		
1422970	2						2/0-10	4-14	B, C	150	150	100	30	60	30	100,000 A		
1423970	3						1-6	6-12	G, H, I	150	150	100	30	60	30	100,000 A		
1431123	1	255	(1) 250 - 6	(1) 250 - 6			250-6	250-6	B, C	300	300	200	100	60	30	100,000 A		
1432123	2						250-1/0	250-1/0	G, H, I	300	300	200	100	60	30	100,000 A		
1433123	3																	
1431124	1	255	(1) 250 - 6	(1) 250 - 6			250-6	250-6	B, C	300	300	200	100	60	30	100,000 A		
1432124	2						250-1/0	250-1/0	G, H, I	300	300	200	100	60	30	100,000 A		
1433124	3																	
1431126	1	310	(1) 350 - 6	(1) 350 - 6			350-1/0	350-1/0	B, C	400	400	400	100	60	30	100,000 A		
1432126	2						350-6	350-6	B, C	300	300	200	100	60	30	100,000 A		
1433126	3						250-1/0	250-1/0	G, H, I	300	300	200	100	60	30	100,000 A		
1431552	1	335	(1) 400 - 6	(4) 2 - 14			400-3/0	2-6	B, C	400	400	400	100	60	30	100,000 A		
1432552	2						400-6	2-10	B, C	300	300	200	100	60	30	100,000 A		
1433552	3						250-1/0	4-10	G, H, I	150	150	100	30	60	30	100,000 A		
1431553	1	335	(1) 400 - 6	(6) 2 - 14			400-3/0	2-8	B, C	500	500	400	200	60	30	100,000 A		
1432553	2						400-6	2-10	B, C	350	350	200	100	60	30	100,000 A		
1433553	3						(1) 6	(2) 12	B, C	350	350	200	100	60	30	100,000 A		
							250-1/0	4-10	G, H, I	150	150	100	30	60	30	100,000 A		
1431554	1	310	(1) 350 - 6	(2) 2/0 - 14			350-3/0	2/0-3	B, C	450	450	400	200	60	30	100,000 A		
1432554	2						350-6	2/0-6	B, C	300	300	200	100	60	30	100,000 A		
1433554	3						250-1/0	1-6	G, H, I	150	150	100	30	60	30	100,000 A		
1431555	1	350	(2) 2/0 - 14	(6) 4 - 14			2/0-2	4-8	B, C	400	400	400	100	60	30	100,000 A		
1432555	2						2/0-6	4-8	B, C	350	350	200	100	60	30	100,000 A		
1433555	3						2/0-6	4-10	B, C	250	250	200	60	60	30	100,000 A		
							(1) 6	(2) 12	B, C	225	225	100	60	60	30	100,000 A		
							1-6	6-14	G, H, I	150	150	100	30	60	30	100,000 A		















High SCCR with Fuse Protection

UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS										UL	FILE UL FILE NO
Marathon Catalog #	Poles	Amps	Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) ⁽²⁾			Overcurrent Protection Fuse Required Class/Max Amp Rating ⁽³⁾						SCCR, RMS SYM Amps ⁽¹⁾		
			Line	Load	Line	Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC			
1431559	1	310	(1) 350 - 6	(1) 3/8 - 16 x 1 1/8			350-4	350-4	B, C	400	400	400	100	60	30	65,000 A		
1432559	2						250-1/0	250-1/0	G, H, I	300	300	200	100	60	30	65,000 A		
1433559	3																	
1431587	1	380	(1) 500 - 4	(3) 2 - 14			500-3/0	350-6	B, C	500	500	400	200	60	30	100,000 A		
1432587	2						500-4	350-10	B, C	200	200	200	100	60	30	100,000 A		
1433587	3						(1) 350 - 6	350-2	250-1/0	G, H, I	150	150	100	30	60	30	100,000 A	
																		350-2
1431953	1	380	(1) 500 - 4	(6) 2 - 14			500-3/0	2-8	B, C	400	400	400	200	60	30	100,000 A		
1432953	2						500-4	2-10	B, C	300	300	200	100	60	30	100,000 A		
1433953	3						250-1/0	4-10	G, H, I	150	150	100	30	60	30	100,000 A		
1431955	1	350	(2) 2/0 - 14	(6) 4 - 14			2/0-2	4-8	B, C	400	400	400	100	60	30	100,000 A		
1432955	2						2/0-6	4-8	B, C	350	350	200	100	60	30	100,000 A		
1433955	3						4-10	10-14	G, H, I	150	150	100	30	60	30	100,000 A		
1441551	1	380	(1) 500 - 4	(6) 2 - 14			500-3/0	2-8	B, C	500	500	400	200	60	30	100,000 A		
1442551	2						500-4	2-10	B, C	200	200	200	100	60	30	100,000 A		
1443551	3						350-2	4-14	G, H, I	150	150	100	30	60	30	100,000 A		
1441560	1	335	(1) 400 - 6	(8) 2 - 14			400-3/0	2-8	B, C	400	400	400	200	60	30	100,000 A		
1442560	2						400-6	2-10	B, C	200	200	200	100	60	30	100,000 A		
1443560	3						250-1/0	4-14	G, H, I	150	150	100	30	60	30	100,000 A		
1441557	1	420	(1) 600 - 4	(1) 600 - 4			600-2	600-2	B, C	600	600	-	-	-	-	50,000 A		
1442557	2						600-2	600-2	B, C	400	400	400	200	60	30	100,000 A		
1443557	3						350-2	350-2	G, H, I	400	400	400	200	60	30	100,000 A		
1451129	1	620	(2) 350 - 4	(2) 350 - 4			350-4	350-4	B, C	450	450	400	200	60	30	100,000 A		
1452129	2						350-4	350-4	B, C	600	600	-	-	-	-	50,000 A		
1453129	3						250-2	250-2	G, H, I	600	600	-	-	-	-	50,000 A		
																	250-2	250-2

High SCCR with Fuse Protection

UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS										UL	FILE UL FILE NO
Marathon Catalog #	Poles	Amps	Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) ⁽²⁾			Overcurrent Protection Fuse Required Class/Max Amp Rating ⁽³⁾						SCCR, RMS SYM Amps ⁽¹⁾		
			Line	Load	Line	Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC			
1451301	1	760	(2) 500 - 4	(2) 500 - 4			500-4	500-4	B, C	500	500	400	200	60	30	100,000 A		
1452301	2						350-2	350-2	G, H, I	500	500	400	200	60	30	100,000 A		
1453301	3																	
1451552	1	380	(1) 500 - 4	(12) 2 - 14			500-3/0	2-6	B, C	400	400	400	200	60	30	100,000 A		
1452552	2						500-4	2-10	B, C	250	250	200	100	60	30	100,000 A		
1453552	3						350-2	4-6	G, H, I	400	400	400	200	60	30	100,000 A		
							350-2	4-10	G, H, I	250	250	200	200	60	30	100,000 A		
1451579	1	380	(1) 500 - 4	(6) 2/0 - 14			500-3/0	2/0-6	B, C	400	400	400	100	60	30	100,000 A		
1452579	2						500-4	2/0-10	B, C	200	200	200	100	60	30	100,000 A		
1453579	3						350-2	1-6	G, H, I	400	400	400	100	60	30	100,000 A		
							350-2	1-10	G, H, I	250	250	200	100	60	30	100,000 A		
1451586	1	760	(2) 500 - 4	(8) 2/0 - 14			500-250	2/0-4	B, C	600	600	400	200	60	30	100,000 A		
1452586	2						500-4	2/0-10	B, C	350	350	200	100	60	30	100,000 A		
1453586	3						350-250	1-4	G, H, I	600	600	400	200	60	30	100,000 A		
							350-4	6-10	G, H, I	350	350	200	100	60	30	100,000 A		
1451592	1	760	(2) 500 - 4	(12) 4 - 14			500-250	4-8	B, C	400	400	200	100	60	30	100,000 A		
1452592	2						500-4	4-10	B, C	350	350	200	100	60	30	100,000 k		
1453592	3						350-250	6-8	G, H, I	400	400	200	100	60	30	100,000 k		
							350-4	6-10	G, H, I	350	350	200	100	60	30	100,000 k		
1451594	1	380	(1) 500 - 4	(8) 2 - 14			500-3/0	2-8	B, C	500	500	400	200	60	30	100,000 A		
1452594	2						500-4	2-10	B, C	300	300	200	100	60	30	100,000 A		
1453594	3						350-3/0	4-8	G, H, I	500	500	400	200	60	30	100,000 A		
							350-2	4-10	G, H, I	300	300	200	100	60	30	100,000 A		
1451599	1	760	(2) 500 - 4	(2) 3/8 - 16 x 1 5/16			500-4/0	500-4/0	B, C	600	600	400	200	60	30	100,000 A		
1452599	2						500-4	500-4	B, C	400	400	400	100	60	30	100,000 A		
1453599	3						350-4/0	350-4/0	G, H, I	600	600	400	200	60	30	100,000 A		
							350-2	350-2	G, H, I	400	400	400	100	60	30	100,000 A		









High SCCR with Fuse Protection

UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS										UL	FILE UL FILE NO
Marathon Catalog #	Poles	Amps	Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) ⁽²⁾			Overcurrent Protection Fuse Required Class/Max Amp Rating ⁽³⁾						SCCR, RMS SYM Amps ⁽¹⁾		
			Line	Load	Line	Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC			
1451986	1	760	(2) 500 - 4	(8) 2/0 - 14			500-250	2/0-4	B, C	500	500	400	200	60	30	100,000 A		
1452986	2						500-4	2/0-6	B, C	450	450	400	200	60	30	100,000 A		
1453986	3						350-250	1-4	G, H, I	500	500	400	200	60	30	100,000 A		
1451992	1	760	(2) 500 - 4	(12) 2 - 14			350-2	1-6	G, H, I	450	450	400	200	60	30	100,000 A		
1452992	2						500-4	2-10	B, C	400	400	400	200	60	30	100,000 A		
1453992	3						500-250	2-8	B, C	600	600	-	-	-	-	50,000 A		
EPBAP71	1	510	(2) 250 - 6	(2) 250 - 6			350-250	4-10	G, H, I	400	400	400	200	60	30	100,000 A		
							250-1/0	250-1/0	B, C	400	400	400	200	60	30	100,000 A		
							250 - 1/0	250 - 1/0	B, C	600	600	-	-	-	-	50,000 A		
							250-6	250-6	B, C	400	400	400	100	60	30	100,000 A		
EPBAP74	1	335	(1) 400 - 6 (1) 2/0 - 14	(8) 2 - 14			250-1/0	250-1/0	G, H, I	300	300	200	100	60	30	100,000 A		
							400-3/0	2-8	B, C	400	400	400	200	60	30	100,000 A		
							400-6	2-10	B, C	200	200	200	100	60	30	100,000 A		
EPBCP71	1	510	(2) 250 - 6	(2) 250 - 6			400-6	2-10	G, H, I	300	300	200	100	60	30	100,000 A		
							250-1/0	250-1/0	B, C	400	400	400	200	60	30	100,000 A		
							250 - 1/0	250 - 1/0	B, C	600	600	-	-	-	-	50,000 A		
							250-6	250-6	B, C	400	400	400	100	60	30	100,000 A		
EPBCP74	1	335	(1) 400 - 6 (1) 2/0 - 14	(8) 2 - 14			250-1/0	250-1/0	G, H, I	300	300	200	100	60	30	100,000 A		
							400-3/0	2-8	B, C	400	400	400	200	60	30	100,000 A		
							400-6	2-10	B, C	200	200	200	100	60	30	100,000 A		
							(1) 6	(2) 12	B, C	225	225	100	60	60	30	100,000 A		
							400-6	2-10	G, H, I	300	300	200	100	60	30	100,000 A		















High SCCR with Fuse Protection

UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION						HIGH SCCR CONDITIONS										UL	FILE UL FILE NO	
Marathon Catalog #	Poles	Amps	Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) ⁽²⁾			Overcurrent Protection Fuse Required Class/Max Amp Rating ⁽³⁾								SCCR, RMS SYM Amps ⁽¹⁾
			Line	Load	Line	Load	Load	Wire Class	J	T	RK1	RK5	G	CC				
BFPB	2	1605	Lugs or Flexibar				750 - 350 kcmil			1200	600	1200	600	600		100,000 A	Recognized	XCFR2.E62806
	3						10x100x1 - 4x32x1			1200	600	1200	600	600		100,000 A		
	4						750 - 350 kcmil			No Over-Current Protection Device Required						35,000 A		
	5						10x100x1 - 4x32x1			No Over-Current Protection Device Required						35,000 A		
	6						Applicable lugs/Flexibar			No Over-Current Protection Device Required						10,000		
EPBAD21	1	115	(1) 2 - 14	(1) 2 - 14			2-14	2-14	B, C	175	225	100	60	60	30	100,000 A	Listed	QPQS.E309401
							4 - 14 (class G,H,I,K)	4 - 14 (class G,H,I,K)	G, H, I	175	225	100	60	60	30	100,000 A		
EPBAD24	1	115	(1) 2 - 14	(4) 10 - 14			2 - 10	10 - 14	B, C	125	200	100	30	60	30	65,000 A	Listed	QPQS.E309401
							4- 10 (class G,H,I,K)	10 - 14 (class G,H,I,K)	G, H, I	125	200	100	30	60	30	65,000 A		
EPBAD42	1	175	(1) 3/0 - 14	(1) 3/0 - 14			3/0-8	3/0-8	B, C	225	225	200	60	60	30	100,000 A	Listed	QPQS.E309401
EPBAP42							2/0-8	2/0-8	G, H, I	300	300	200	100	60	30	100,000 A		
EPBCD42							3/0-8	3/0-8	B, C	225	225	200	60	60	30	100,000 A		
EPBCP42							2/0-8	2/0-8	G, H, I	300	300	200	100	60	30	100,000 A		













High SCCR with Fuse Protection

UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS										UL	FILE UL FILE NO
Marathon Catalog #	Poles	Amps	Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) ⁽²⁾			Overcurrent Protection Fuse Required Class/Max Amp Rating ⁽³⁾						SCCR, RMS SYM Amps ⁽¹⁾		
			Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC			
EPBAD45	1	175	(1) 3/0 - 14	(4) 2 - 14			3/0-8	2-8	B, C	225	225	200	60	60	30	100,000 A	Listed	QPQS.E309401
							3/0-8	8-14	B, C	100	110	100	30	60	30	100,000 A		
							2/0-8	4-8	G, H, I	225	225	200	60	60	30	100,000 A		
							2/0-8	8-12	G, H, I	100	110	100	30	60	30	100,000 A		
							3/0-10	2-14	G, H, I	60	60	30		50	30	100,000 A		
							(1) 8	(2) 14	G, H, I	225	225	100	60	60	30	100,000 A		
EPBAP45	1	175	(1) 3/0 - 14	(4) 2 - 14			3/0-8	2-8	B, C	225	225	200	60	60	30	100,000 A		
							3/0-8	8-14	B, C	100	110	100	30	60	30	100,000 A		
							2/0-8	4-8	G, H, I	225	225	200	60	60	30	100,000 A		
							2/0-8	8-12	G, H, I	100	110	100	30	60	30	100,000 A		
EPBCD45	1	175	(1) 3/0 - 14	(4) 2 - 14			3/0-8	2-8	B, C	225	225	200	60	60	30	100,000 A		
							3/0-8	8-12	B, C	100	110	100	30	60	30	100,000 A		
EPBCP45	1	175	(1) 3/0 - 14	(4) 2 - 14			2/0-8	4-8	G, H, I	225	225	200	60	60	30	100,000 A		
							2/0-8	8-12	G, H, I	100	110	100	30	60	30	100,000 A		
EPBAP81	1	760	(2) 500 - 4	(2) 500 - 4			500-4	500-4	B, C	600	600	600	200	60	30	100,000 A	Listed	QPQS.E309401
							350-2	350-2	G, H, I	600	600	600	200	60	30	100,000 A		
EPBAP84	1	760	(2) 500 - 4	(8) 2/0 - 14			500-250	2/0-4	B, C	600	600	400	200	60	30	100,000 A	Listed	QPQS.E309401
							500-4	2/0-10	B, C	350	350	200	100	60	30	100,000 A		
							350-250	1-4	G, H, I	600	600	600	200	60	30	100,000 A		
							350-4	1-8	G, H, I	350	350	200	100	60	30	100,000 A		
EPBCP84	1	760	(2) 500 - 4	(8) 2/0 - 14			500-250	2/0-4	B, C	600	600	600	200	60	30	100,000 A	Listed	QPQS.E309401
							500-4	2/0-10	B, C	350	350	200	100	60	30	100,000 A		
							350-250	1-4	G, H, I	600	600	600	200	60	30	100,000 A		
							350-4	1-8	G, H, I	350	350	200	100	60	30	100,000 A		













High SCCR with Fuse Protection

UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS										UL	FILE UL FILE NO
Marathon Catalog #	Poles	Amps	Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) ⁽²⁾			Overcurrent Protection Fuse Required Class/Max Amp Rating ⁽³⁾						SCCR, RMS SYM Amps ⁽¹⁾		
			Line	Load	Line	Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC			
1351605 1352605 1353605	1 2 3	950	(2) 600 - 2	(4) 350 - 6			600 - 2	2/0-10	B, C	400	400	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1351701 1352701 1353701	1 2 3	475	750 - 1/0	750 - 1/0			750-1/0	750-1/0	B, C	600	1200	600	400	60	-	100,000 A	Listed	QPQS.E309401
							535-1/0	535-1/0	G, H, I	600	700	600	200	60	-	100,000 A		
1351702 1352702 1353702	1 2 3	950	(2) 750 - 1/0	(2) 750 - 1/0			750-1/0	750-1/0	B, C	600	1200	600	400	60	-	100,000 A	Listed	QPQS.E309401
							535-1/0	535-1/0	G, H, I	600	700	600	200	60	-	100,000 A		
1351703 1352703 1353703	1 2 3	950	(2) 750 - 1/0	(6) 250 - 6			750-1/0	250-2	B, C	600	700	600	200	60	-	100,000 A	Listed	QPQS.E309401
							750-1/0	250-6	B, C	300	300	200	100	60	-	100,000 A		
							535-1/0	3/0-2	G, H, I	600	700	600	200	60	-	100,000 A		
							535-1/0	3/0-6	G, H, I	300	300	200	100	60	-	100,000 A		
1351704 1352704 1353704	1 2 3	950	(2) 750 - 1/0	(10) 2/0 - 6			750-1/0	2/0-2	B, C	600	700	600	200	60	-	100,000 A	Listed	QPQS.E309401
							750-1/0	2/0-6	B, C	300	300	200	100	60	-	100,000 A		
							535-1/0	1-2	G, H, I	600	700	600	200	60	-	100,000 A		
							535-1/0	1-6	G, H, I	300	300	200	100	60	-	100,000 A		
1351705 1352705 1353705	1 2 3	950	(2) 750 - 1/0	(3) 250 - 6 (12) 2 - 14			750-1/0	250-2	B, C	600	700	600	200	60	-	100,000 A	Listed	QPQS.E309401
							750-1/0	250 - 6	B, C	300	300	200	100	60	-	100,000 A		
							750-1/0	2 - 6 (#2 opening)	B, C	300	300	200	100	60	-	100,000 A		
							535-1/0	3/0-2	G, H, I	600	700	600	200	60	-	100,000 A		
							535-1/0	3/0-6	G, H, I	300	300	200	100	60	-	100,000 A		
							535-1/0	4 - 6 (#2 opening)	G, H, I	300	300	200	100	60	-	100,000 A		









High SCCR with Fuse Protection

UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION						HIGH SCCR CONDITIONS										UL	FILE UL FILE NO	
Marathon Catalog #	Poles	Amps	Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) ⁽²⁾			Overcurrent Protection Fuse Required Class/Max Amp Rating ⁽³⁾								SCCR, RMS SYM Amps ⁽¹⁾
			Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC			
1351706	1	950	(2) 750 - 1/0	(5) 250 - 6			750-1/0	250-2	B, C	600	600	600	200	60	-	100,000 A	Listed	QPQS.E309401
1352706	2						750-1/0	250 - 6	B, C	300	300	200	100	60	-	100,000 A		
1353706	3						750-1/0	2 - 6 (#2 opening)	B, C	300	300	200	100	60	-	100,000 A		
		535-1/0	3/0-2	G, H, I	600	600	600	200	60	-	100,000 A							
		535-1/0	3/0-6	G, H, I	300	300	200	100	60	-	100,000 A							
		535-1/0	4 - 6 (#2 opening)	G, H, I	300	300	200	100	60	-	100,000 A							
1351707	1	950	(2) 750 - 1/0	(4) 3/0 - 6			750-1/0	3/0-2	B, C	600	700	600	200	60	-	100,000 A	Listed	QPQS.E309401
1352707	2						750-1/0	3/0 - 6	B, C	300	300	200	100	60	-	100,000 A		
1353707	3						750-1/0	2 - 6 (#2 opening)	B, C	300	300	200	100	60	-	100,000 A		
		535-1/0	2/0-2	G, H, I	500	500	400	200	60	-	100,000 A							
		535-1/0	2/0-6	G, H, I	300	300	200	100	60	-	100,000 A							
		535-1/0	4 - 6 (#2 opening)	G, H, I	300	300	200	100	60	-	100,000 A							
1351708	1	950	(2) 750 - 1/0	(8) 3/0 - 6			750-1/0	3/0-2	B, C	600	700	600	200	60	-	100,000 A	Listed	QPQS.E309401
1352708	2						750-1/0	3/0 - 6	B, C	300	300	200	100	60	-	100,000 A		
1353708	3						535-1/0	3/0-2	G, H, I	500	500	400	200	60	-	100,000 A		
		535-1/0	2/0-6	G, H, I	300	300	200	100	60	-	100,000 A							
FPB23570	3	175	2/0-6	4-14			2/0-6	4-14	B, C	200	200	200	100	60	30	100,000 A	Listed	QPQS.E309401
FPB23572	3	175	2/0-6	2/0-6			2/0-6	2/0-6	B, C	200	200	200	100	60	30	100,000 A	Listed	QPQS.E309401
FPB23574	3	175	2/0-6 2/0-10	2/0-6 2/0-10			2/0-6	2/0-6	B, C	200	200	200	100	60	30	100,000 A	600	QPQS.E309401
							8-10	8-10	B, C	100	100	100	30	60	30	100,000 A		

High SCCR with Fuse Protection

UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS											
Marathon Catalog #	Poles	Amps	Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) ⁽²⁾			Overcurrent Protection Fuse Required Class/Max Amp Rating ⁽³⁾						SCCR, RMS SYM Amps ⁽¹⁾	UL	FILE UL FILE NO
			Line	Load	Line	Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC			
FPB23580	3	175	2/0-6	4-10			2/0-6	4-14	B, C	200	200	200	100	60	30	100,000 A	600	QPQS.E309401
FPB33553	3		400-3/0	2-8			400-3/0	2-8	B, C	400	400	400	100	60	30		600	QPQS.E309401
			2/0-2	2-14			B, C	200	200	200	100	60	30	100,000 A				
FPB33588	3	420	600-3/0	1/0-8			600-3/0	1/0-8	B, C	450	450	400	100	60	30		600	QPQS.E309401
			600-2	1/0-10			B, C	200	200	200	100	60	30	100,000 A				
FPB33595	3	420	600-3/0	4-8			600-3/0	4-8	B, C	450	450	400	100	60	30		600	QPQS.E309401
			600-2	4-10			B, C	200	200	200	100	60	30	100,000 A				

(1) Short-circuit current ratings may be marked on the block or instructions provided with the terminal block

(2) Size range of conductors suitable to maintain noted SCCR

(3) Maximum size of line side overcurrent protection to provide noted SCCR